



3175 MACARTHUR BLVD. • NORTHBROOK, IL • 60062
 847-459-1460 • FAX 847-714-9443
 www.lund-industries.com
 www.data-carts.com

SSTB-2042 & LGV-T40, LGV-1540 and LGV-1636 FPI-U-RM Raised Mount Vault Instructions

- 1) Remove passenger and driver side plastic 3rd row seat belt trim panels. (*see fig. 1*)
- 2) Remove (2) factory bolts with 15mm socket. Place each side brace in and loosely attach for later adjustment. (*see fig. 2*)
- 3) Remove (2) factory bolts on cargo floor with 10mm socket. Set aside as they will be replaced with longer bolts for the installation.
- 4) Attach elevated mounts with supplied 5/8" shims and M8 x 100mm bolts and washers. Loosely attach for later adjustment. (*see fig. 3*) Note: there are several mounting holes in the brackets for fore and aft positioning of the box. Choose which ones work best for you.
- 5) Attach the side brace to the elevated mount with supplied 3/8" carriage bolts, nylock nuts and washers. (*see fig. 4*)
- 6) Set a small level on top and adjust accordingly and fully tighten each nut and bolt. (*see fig. 5*)
- 7) Install the (2) cross braces with supplied 1/4"-20 hardware to complete the base installation. Position the box on top of the base to assure proper fit before tightening hardware.
- 8) Set either the SSTB-2042 or the LGV on top and measure accordingly for desired location.
- 9) **SSTB-2042 only:** Place SSTB-2042 on the raised mount and use supplied 3/8" x 3/4" Hex bolts and washers to secure the SSTB-2042 to the raised mount.
- 10) **LGV-T40 & LGV-1540 only:** Use supplied 5/16" hardware to attach. Put LGV in desired location and mark bottom of box where holes need to be drilled. Remove LGV for easy drilling of marked holes with a 5/16" drill bit. Place back on mount and install with 5/16" hardware.
- 11) **LGV-1636 only:** Use supplied "L" brackets. Install "L" bracket into pems in side of box and attach other end of "L" brackets to mount with supplied 5/16" hardware.



Fig. 1



Fig. 2



Fig. 3



Fig. 4



Fig. 5



Fig. 6