


SB-87-TP

DATE	CHANGES	INTL	REV
08.15.11	Original	TWH	1.0
09.08.11	Added spacebar and mouse button lines	TWH	1.1
10.12.11	Added height w/out feet	TWH	1.2



KEY SWITCH

MATERIAL: Industrial Silicone Rubber
 LIFE: Greater Than 10 Million Cycles
 TRAVEL: 0.055 in.
 ACTUATION FORCE: 7.05 oz. +/- 1.06oz (200g +/- 30g)
 FEEDBACK: Tactile with Mechanical Snap

TEMPERATURE RANGE

STORAGE: -40°F to +194°F (-40°C to +90°C)
 OPERATING: -40°F to +158°F (-40°C to +70°C)

VIBRATION

POWER SPECTRAL DENSITY: .04g/HZ
 FREQUENCY RANGE: 20Hz-2Khz
 DURATION OF TEST PER AXIS: 3 hours

POWER

USB: 200mA@5V (from CPU port)

HUMIDITY

100% Humidity Resistant

SHOCK

3 X 11 ms pulses of 50g on each of 3 axis

WEIGHT

1.4 ± 0.10 lbs (0.6 ± 0.05 kg)

PROPRIETARY AND CONFIDENTIAL



iKey, Ltd.
 2621 Ridgpoint Dr. Suite 235
 Austin, Texas 78754

©2011 iKey, Ltd.

Voice: (512) 837-0283
 Fax: (512) 927-8530

Part Number: SB-87-TP

Drawing Title: SB-87-TP-MKT (REV 1.2)

Drawing Number: PAD0267

Revision: 1.2

Sheet: 1 OF 1

Date: 10.12.2011

TWH